

Technical Data Sheet (TDS):

Specifications

| | | | |
|--------------------------|------------------|----------------------|---|
| Model: | STJGG101 | Power: | 9W |
| Light Source: | Luminus | Input Voltage: | AC 220~240V, 50/60Hz |
| Colour Rendering Index: | Ra≥95 | Main Material: | Aluminium |
| Driver: | Remote | Installation Method: | track mounted |
| Luminaire Luminous Flux: | Lumen | Luminous Efficiency: | Lumen/W |
| Structure: | Adjustable angle | Beam Angle: | <input type="checkbox"/> 15° <input type="checkbox"/> 24° <input type="checkbox"/> 36° |
| IP Rating: | IP 20 | Colour Temperature: | <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 3500K <input type="checkbox"/> 4000K |
| Dimensions: | Ø33.5*L110mm | Cutout: | / |
| Insulation Class: | Class 3 | Optics Accessories: | — |

Intelligent Control: ☐ (Non-Dim) ☐ (Triac) ☐ DALI ☐ 0-10V ☐ PWM ☐ DMX512

Finish: ☐ WH ☐ BK ☐ WH+CH ☐ WH+BK ☐ WH+GD