


Technical Data Sheet (TDS):

Specifications			
Model:	ST-JG-XG02	Power:	5W
Light Source:	Luminus	Input Voltage:	AC 220~240V, 50/60Hz
Colour Rendering Index:	Ra≥95	Main Material:	Aluminium
Driver:	Remote	Installation Method:	Recessed
Luminaire Luminous Flux:	260 Lumen	Luminous Efficiency:	52 Lumen/W
Structure:	Adjustable	Beam Angle:	☐ 10° ☐ 15° ☐ 24° ☐ 36° ☐ 10*45°
IP Rating:	IP 20	Colour Temperature:	☐ 2700K ☐ 3000K ☐ 3500K ☐ 4000K
Dimensions:	44*44*55mm	Cutout:	/
Insulation Class:	Class 3	Optics Accessories:	—
Intelligent Control:	☐ (Non-Dim) ☐ (Triac) ☐ DALI ☐ 0-10V ☐ PWM ☐ DMX512		
Finish:	☐ WH ☐ BK ☐ WH+CH ☐ WH+BK ☐ WH+GD ☐ Bk+GD		

Photometric and Luminous Intensity Distribution Curve



H(m)	E0(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	1576.33	0.37/0.36	0.1	760.15
2.0	394.08	0.73/0.72	0.4	182.54
3.0	175.15	1.10/1.08	1.0	81.13
4.0	98.52	1.46/1.44	1.7	45.63
5.0	63.05	1.83/1.80	2.7	29.21