


Technical Data Sheet (TDS):

Specifications			
Model:	ST-JG-XQ04C	Power:	5W
Light Source:	Luminus	Input Voltage:	AC 220~240V, 50/60Hz
Colour Rendering Index:	Ra≥95	Main Material:	Aluminium
Driver:	Remote	Installation Method:	Recessed
Luminaire Luminous Flux:	262 Lumen	Luminous Efficiency:	52 Lumen/W
Structure:	Fixed	Beam Angle:	☐ 10° ☐ 15° ☐ 24° ☐ 36° ☐ 10*45°
IP Rating:	IP 20	Colour Temperature:	☐ 2700K ☐ 3000K ☐ 3500K ☐ 4000K
Dimensions:	44*44*62mm	Cutout:	/
Insulation Class:	Class 3	Optics Accessories:	—
Intelligent Control:	☐ (Non-Dim) ☐ (Triac) ☐ DALI ☐ 0-10V ☐ PWM ☐ DMX512		
Finish:	☐ WH ☐ BK ☐ WH+CH ☐ WH+BK ☐ WH+GD ☐ Bk+GD		

Photometric and Luminous Intensity Distribution Curve



H(m)	E0(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	1753.15	0.35/0.35	0.1	991.74
2.0	438.29	0.71/0.71	0.4	247.94
3.0	194.79	1.06/1.06	0.9	110.19
4.0	109.57	1.42/1.41	1.6	61.98
5.0	70.13	1.77/1.76	2.5	39.67